

PRODUCT INFORMATION

13" Triple Outdoor E-paper Display

Ruggedized IP65 rated outdoor e-paper displays are supplied in an aluminium enclosure with toughened front glass, optimized for pole mount or to any other fixed surface. With wireless, battery and solar capabilities as standard, all models come with optional illumination, interactive functions and text-to-speech modules


GENERAL

Dimension (L x H x W)	274 x 1086 x 59 mm
Weight	16.7 kg (36.8 lb)
Mounting type	Custom pole clamp with security fixing
Colour	RAL 9006 Custom colours also available

DISPLAY

Display resolution	1200 x 4800 pixels
Active display area	203 x 810 mm
Pigment	Greyscale (16 levels of grey)
Display type	Reflective
Illumination	Embedded LED front illumination, adjustable
Ambient light sensor	Optional

ENVIRONMENT

Operating temperature (Without heaters)	Greyscale: -20°C to +70°C (-4°F to +158°F)
Protection	IP65

CONNECTIVITY

Communication	Mobile network or WiFi or Ethernet
Mobile network	3G or optional 4G/LTE
Mobile network antenna	Internal (external antenna optional)
WiFi (optional)	Dual band (2.4/5 GHz) 802.11 ac/b/g/n
WiFi antenna (optional)	Internal / external
Ethernet (optional)	10/100/1000 Mbps

ELECTRICAL

Power supply	12 V DC (from AC mains via power supply) or 12 V DC solar panel
Power consumption (1 min data update)	50 mA (without illumination) 80 mA (illuminated)
Power consumption (Text-to-speech)	70 mA (without illumination) 100 mA (illuminated)
Power consumption (User interaction)	80 mA (without illumination) 110 mA (illuminated) Support for full shutdown with timer
Power supply connector	Male 5-pin circular waterproof

CERTIFICATIONS

Certificate of Conformity, Environmental, Electromagnetic Compatibility (EMC), Radio Equipment Directive (RED), Ingress Protection Rating (min IP65), Impact Protection Rating (min IK08)

MAAHANTUONTI JA JÄLLEENMYyntI

Sx3-Group Oy
Sx3-Group Oy

Lahdenkatu 15 A
15110 LAHTI, FINLAND

Iipo Pulli

Sähköposti: iipo.pulli@sx3.fi
Puhelin: +358 (0)500 716 110